

SIP GRUU offering

- Create a configuration file according to the XML file format e.g. **gruu.cfg**
- File content:

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
```

```
<!-- Generated by sipXecs: http://www.sipfoundry.org/
```

```
Instructions for integrating new configuration file content into sipXconfig:
```

```
http://wiki.sipfoundry.org/display/xecsdev/Adding+Polycom+SoundPoint+IP+New+Configuration+File+Content+into+sipXconfig
```

```
-->
```

```
<polycomConfig xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="polycomConfig.xsd">
```

```
<reg reg.1.gruu="1"/>
```

```
</polycomConfig>
```

- Upload the file either manually to **/var/sipxdata/configserver/phone/profile/tftproot/** or through the Admin Portal -> Devices -> Device files
- Apply this configuration files to the desired devices: Devices -> Phones -> <MAC> -> Custom configuration and fill in the name of the file (e.g: **gruu.cfg**)
- Send profiles

Note: This will be improved as to be configurable from Admin Portal per device

Documentation on GRUU :<http://tools.ietf.org/html/draft-ietf-sip-gruu-15>