

sipXcom 19.04

May 10, 2019

Summary

eZuce is pleased to announce the General Availability of sipXcom 19.04.

There are again two releases for sipXcom 19.04, one for CentOS 6 and one for CentOS 7. The documentation around Installations and Downloads is being updated now with CentOS 7 as the recommended OS moving forward. We'll also update the video to cover CentOS 7 Minimal installation. While this is a relatively small update, there are a few interesting things to point out.

When a user is deleted from the system, the configuration services will now go through all phones and remove that user from the phones and re-send phone profiles. If that was the only user on the phone, the phone will go back to the auto-provision ID. What we were finding is that administrators were deleting users but not re-sending phone profiles. This would result in traffic floods of SIP traffic with bad subscribes to MWI and invalid registrations to the server.

The new Polycom VVX '50' series phones are now supported for configuration as well as auto-provisioning. Firmware versions 5.9.0 and later are supported.

Also, mongoDB has been updated to 3.6.11. This has had a positive effect in recovery from a node outage. The new mongod seems much more resilient.

Please note that this will be the last release for CentOS 6. As of version 19.08 we will only be releasing sipXcom for CentOS 7! To go from a CentOS 6 based system to a CentOS 7 based system will require a backup and restore to a fresh CentOS 7 installation. As such a parallel install will be recommended.

We've also decided to put the container (Docker) work on hold for now. There were complexities around networking and implementation that we didn't feel warranted the effort involved to work past them. Additionally, there wasn't significant customer demand to warrant the effort at this point. We're pushing ahead with some newer features instead.

Highlights

sipXcom New Features:

- Support for Polycom VVX 150, 250, 350 and 450
- Alarm for Certificate Expiration
- Make mongoDB cache size configurable
- Remove user from phones automatically after user deleted from system

sipXcom Improvements:

- Sort alarms alphabetically
- Upgrade mongod to 3.6.11
- Add http provisioning option to DHCP configuration

Notes

1. Full Beta Release Notes with installation information are located here: [19.04 Full Release Notes](#)
2. The regular release of 19.04 will have the ability to upgrade from earlier versions using the upgrade script used in 18.04. For the purposes of this beta release, please only do upgrades from 18.04 if you test systems are on a version earlier than 18.04, upgrade to 18.04 first.

Who Should Install?

This release is recommended for all production installations.

New software releases are made at a rate of two to four releases a year. Releases are numbered in the <yy>.<mm>.<uu> format where <yy> and <mm> designate the year and the month, respectively, in which a release is made generally available. Where applicable, <uu> corresponds to an update release relative to a general release on which fixes are made available.

Questions

Please post to the sipXcom-users google group if you have questions.

<https://groups.google.com/forum/#!forum/sipxcom-users>

Issues Sorted by Issue Number

Jira #	JIRA Name	RN Content	Enhancement/Fix/Known Issue	Keywords
SI P X-753	Add support for Polycom VVX 150, 250, 350 and 450	Polycom is adding some new VVX phones to their lineup. This is mostly a hardware refresh. Firmware 5.8.x and later supported.	Enhancement	Polycom
SI P X-755	Add alarm for Certificate expiration	Add a system alarm called Certificate_Expiration that generates an alarm at 2 weeks before any system certificate is to expire.	Enhancement	Alarms
SI P X-758	Missing user and password field for Grandstream https conf file authentication	An administrator would like to use an external provisioning server that serves profiles through https using user password authentication, the problem is that in the profiles for the upgrade section there are options for user and password for firmware but not for config which needs to be kept safe more than firmware.	Enhancement	Grandstream
SI P X-763	Alarms should be grouped and in alphabetical order	Alarms in the administration portal should be logically grouped and in alphabetical order, so that related alarms can be displayed adjacent to each other. Now the order seems random and it is hard to find anything except by searching. Alphabetical ordering would put for example CPU_THRESHOLD_EXCEEDED and CPU_THRESHOLD_RECOVERED next to each other, and so on, since the alarm name is hierarchical. Same for MONGO alarms and so on.	Enhancement	Alarms
SI P X-766	Make mongodb cache size configurable	Make mongodb cache size configurable in Admin GUI. System -> Database -> Settings. This is beneficial for systems with small amounts of memory.	Enhancement	MongoDB
SI P X-780	upgrade mongodb to 3.6.9	Upgrade mongodb to version 3.6.9 as resilience is improved. Tests for a customer who wants to upgrade to 3.6 revealed that the upgrade from 3.4 to 3.6 is straightforward and can be done in place. This will also fix, among others, an issue where Mongo could not recover sometimes after the machine was shut down forcibly / powered off and the only solution was to delete the database and database files and replicate again. This was due to an empty storage.bson file: https://jira.mongodb.org/browse/SERVER-30836 The 3.6 version also adds performance improvements. https://docs.mongodb.com/manual/release-notes/3.6-changelog/ "Always-on write availability Retryable writes reduces the error handling you have to implement in your code. The MongoDB drivers will now automatically retry write operations in the event of transient network errors or primary replica elections, while the server enforces exactly-once semantics." Recommended version by Mongo developers is 3.6.9, tested OK, storage.bson bug seems fixed, tested by multiple power offs of nodes, re-elections run smoothly and cluster comes back online with improved speed vs. 3.4 version, even before all services are loaded. RPMS: https://repo.mongodb.org/yum/redhat/6/mongodb-org/3.6/x86_64/RPMS/	Enhancement	MongoDB
SI P X-781	Enable autoprovisioning of new Polycom VVX 150,250,350 and 450 phones	The new Polycom VVX 150,250,350 and 450 phones fail to autoprovision. Investigation has found that the system does not generate configuration files because it does not recognize the user agent. "2018-12-20T12:43:06.694000Z":262::INFO:centos7.juliu.test:SocketListener1-1:00000000:Servlet:"GET /64167f3a750d-sipx-applications.cfg User-Agent: FileTransport PolycomVVX-VVX_450-UA/5.9.0.9373 Type/Application" "2018-12-20T12:43:06.695000Z":263::DEBUG:centos7.juliu.test:SocketListener1-1:00000000:Servlet:"Un-recognized user-agent or path. Redirecting to sipXconfig." With manual generation of configuration files the phones work fine. It seems that the servlet source code should be updated: https://github.com/sipXcom/sipxecs/blob/release-18.12/sipXprovision/src/org/sipfoundry/sipxprovision/auto/Servlet.java also https://github.com/sipXcom/sipxecs/blob/release-18.12/sipXpolycom/src/sipxplugin.beans.xml No. of lines: VVX 150: 2 VVX 250: 4 VVX 350: 6 VVX 450: 12	Enhancement	Polycom
SI P X-782	Clean up and update Polycom config files	Config file templates for Polycom phones are outdated and give out many errors.	Enhancement	Polycom
SI P X-783	CF engine doesn't trigger when Admin Settings are changed in UI	Changing SELinux setting in UI doesn't trigger CF engine to modify /etc/selinux/config file.	Fix	Config

SI P X- 7 84	Wrong title in About window	There is a wrong title in About window.	Fix	Co nfig
SI P X- 7 91	Enhancement: remove user from phone automatically and send profiles upon deletion	As summary describes, enhancement request to automatically remove the user from any assigned phones upon being deleted from sipxconfig. Should also be the case with LDAP if user is set to be deleted or suspended from the system. Should also remove any shared lines or lines with presence subscribed. When the administrator deletes a user, the administrator should be prompted letting them know that the user will be deleted from the system and removed from any system managed phones.	Enhancement	Co nfig
SI P X- 7 92	Populate SIP Domain in the Outbound Proxy field of Shared Lines for HA	In an HA cluster, the Phone->SIP Lines->Outbound proxy field must be provisioned with the SIP domain name (e.g. lptest.com when server names are pbx.lptest.com , pbx2.lptest.com , pbx3.lptest.com) for shared lines, and not the Phones->MAC Address->SIP Servers-> Servers field. Otherwise failover to the secondary servers for private and shared lines to the secondary servers does not work when the primary server is down. In the Polycom Release 5 system administration panel, follow the setup for the Genband MADN-SCA features. The reg.x.outboundproxy.address should be used as the IP address of the SIP server for shared lines.	Fix	Co nfig
SI P X- 8 01	TFTP service not properly configured on CentOS 7	TFTP service is not properly configured on CentOS 7 version. It starts in a wrong root directory and doesn't serve config files.	Fix	Co nfig
U C -4 5 40	zen 7181: voicemail fwd with comment to email	Customer requested an improvement to the voicemail -> email forwarding: "It looks like if you press 5 to forward a copy of a voicemail, and record additional comments, and the destination mailbox has email forwarding enabled, then the email that gets sent out with the voicemail attached doesn't contain the comments. If you check the forwarded message using the phone you hear the comments, but the WAV file attached to the email doesn't have the comments."	Fix	Vo ice m ail
U C -4 6 24	zen 7314 : http provisioning option to dhcp config	An administrator would like to easily configure our dhcp service to add http provisioning options. Customer requested .. : If I check the box "Polycom HTTPS provisioning" in System -> DHCP, there is a new line in /etc/dhcp/dhcpd.conf: option option-160 "https://sipxecs.XXX.com/phoneprov"; When I uncheck that box, that line disappears, so the phone appears to use FTP. It would be good to have a 3rd option to use http, and wondering if that should be the default option. Another thing I discovered, when I uncheck User -> Hoteling -> Enable, then try to log in to a phone, the log says hoteling is not enabled for the user, but it the phone still logs them in fine: "2017-11-03T20:08:55.316000Z":40:JAVA:INFO:sipxecs.XXX.com:P2-17:00000000:HotelingServlet:"Getting configuration for phone: 64167f083e6b; user:1341" "2017-11-03T20:08:55.317000Z":41:JAVA:ERR:sipxecs.XXX.com:P2-17:00000000:HotelingServlet:"Hoteling is not enabled for user: 1341" I'm guessing maybe the configuration files don't get deleted. Any suggestions on this, or can we file a JIRA? I was able to get hoteling to work for the users that wouldn't work, I'm not sure how though. It doesn't seem to be related to being a Reach agent or the group it was in, I didn't change those, but there was an old Jitsi phone provisioned that may have interfered (it was named the same as the user).	Enhancement	Co nfig
U C -4 7 41	zen 7856 / 7858 - 18.04 postgresql password change causes issues	Customer upgraded to 18.04 and changed postgresql password in system -> admin. This seems to have broken hotel. Advised customer to remove postgresql password, which fixed hotel, but broke CDR. Dev requested from customer .. "callresolver log says: "2018-07-23T10:59:09.226647Z":2:CDR:ERR:sip01.ipt.prod.int.phx2.XXX.com:main:00000000.cdr:"cse_reader.rb:: Loss of connection to database #<struct DatabaseUrl database='SIPXCDR', port=5432, host='sip03.ipt.prod.int.phx2.XXX.com', adapter='postgresql', username='postgres', password='>'> - retrying to connect after sleep" "2018-07-23T10:59:09.403025Z":3:CDR:ERR:sip01.ipt.prod.int.phx2.XXX.com:main:00000000.cdr:"cse_reader.rb:: Loss of connection to database #<struct DatabaseUrl database='SIPXCDR', port=5432, host='sip01.ipt.prod.int.rdu2.XXX.com', adapter='postgresql', username='postgres', password='>'> - retrying to connect after sleep" password used by callresolver is retrieved from: config.fetch('SIP_CALLRESOLVER_DB_PASSWORD', " so we need also file: /etc/sipxpbx/callresolver-config specifically, field: SIP_CALLRESOLVER_DB_PASSWORD" .. and customer replied : That was the issue, seems password removal was not propagated. On core: SIP_CALLRESOLVER_DB_PASSWORD : but few servers had password = XXXX sipxagent fixed it.	Fix	Co nfig
U C -4 7 51	CSR has the wrong organization name	When using the Uniteme WebUI to create a CSR it ignores the user input for the organization and inputs the default instead. See attached images for example.	Fix	Co nfig
U C -4 7 78	sipxagent.log does not have timestamps	The cfengine sipxagent.log does not have timestamps, which makes it difficult to troubleshoot. There should be timestamps added to the log, otherwise we are just guessing what happened when. This can be achieved by adding -l (low case L) or --timestamp option	Enhancement	Co nfig

UC-4798	apache rewrites and provisioning files	When attempting to download custom configuration files phones will get a different result depending on the path specified in dhcp option 160. For example, phone will get a different result depending on the path requested from /phoneprov/custom.cfg to /custom.cfg.	Fix	Config
---------	--	---	-----	--------