

# Hunt Group API

## Hunt Groups

### Get all hunt groups

Example:

```
curl -v -k -X GET https://superadmin:password@192.168.1.31/sipxconfig/api/callgroups
```

### Get all huntgroups that have extension starting with a prefix

Example:

```
curl -v -k -X GET https://superadmin:password@localhost/sipxconfig/api/callgroups/prefix/33
```

### Get call group given extension

Example:

```
curl -v -k -X GET https://superadmin:password@localhost/sipxconfig/api/callgroups/3399
```

### Create a hunt group

Example:

```
curl -v -k -X POST -H "Content-Type: application/json" -d '{"name":"pppl","extension":"4444","description":"","enabled":true,"did":null,"ringBeans":[],"fallbackDestination":null,"voicemailFallback":true,"userForward":true,"useFwdTimers":false}' https://superadmin:password@localhost/sipxconfig/api/callgroups
```

### Duplicate hunt group extension as new hunt group with a different extension

Example:

```
curl -v -k -X POST https://superadmin:password@localhost/sipxconfig/api/callgroups/3399/duplicate/55665
```

### Rotate rings for hunt group

Example:

```
curl -v -k -X POST https://superadmin:password@localhost/sipxconfig/api/callgroups/3399/rotate/3
```

### Update hunt group with extension

Example:

```
curl -v -k -X PUT -H "Content-Type: application/json" -d '{"name":"pppl","extension":"4444","description":"kkkkk","enabled":true,"did":null,"ringBeans":[],"fallbackDestination":null,"voicemailFallback":true,"userForward":true,"useFwdTimers":false}' https://superadmin:password@localhost/sipxconfig/api/callgroups/4444
```

### Delete hunt group

**Example:**

```
curl -v -k -X DELETE https://superadmin:password@localhost/sipxconfig/api/callgroups/3399
```