

My Buddy

- [View My buddy settings](#)
- [View or modify My buddy settings](#)

View My buddy settings

Available in 14 starting with 14.10

Resource URI: /imbot/settings

Default Resource Properties:

The resource is represented by the following properties when the GET request is performed:

Property	Description

Specific Response Codes: N/A

HTTP Method: GET

Retrieves a list with all the My buddy settings in the system.

Example: XML format

```
<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<Settings>
  <Setting>
    <path>imbot/log.level</path>
    <type>enum</type>
    <options>
      <entry>
        <key>NOTICE</key>
      </entry>
      <entry>
        <key>CRIT</key>
      </entry>
      <entry>
        <key>EMERG</key>
      </entry>
      <entry>
        <key>WARNING</key>
      </entry>
      <entry>
        <key>ERR</key>
      </entry>
      <entry>
        <key>INFO</key>
      </entry>
    </options>
  </Setting>
</Settings>
```

```
</entry>
<entry>
<key>ALERT</key>
</entry>
<entry>
<key>DEBUG</key>
</entry>
</options>
<value>NOTICE</value>
<defaultValue>NOTICE</defaultValue>
<label>Logging Level</label>
</Setting>
<Setting>
<path>imbot/_imbot.paUserName</path>
<type>string</type>
<value>mybuddy</value>
<defaultValue>mybuddy</defaultValue>
<label>IM ID</label>
<description>The ID under which ImBot feature is visible in the contact list.</description>
</Setting>
<Setting>
<path>imbot/imbot.paPassword</path>
<type>string</type>
<label>IM password</label>
<description>If IM server is configured to use LDAP you need to assign a dedicated account to play MyBuddy role. Set MyBuddy's password accordingly with LDAP account password. Leave the default password if IM server is not configured to use LDAP.</description>
</Setting>
</Settings>
JSON format
{
settings: [3]
0: {
path: "imbot/log.level"
type: "enum"
options: {
NOTICE: null
CRIT: null
EMERG: null
WARNING: null
ERR: null
INFO: null
```

```

ALERT: null
DEBUG: null
}-
value: "NOTICE"
defaultValue: "NOTICE"
label: "Logging Level"
description: null
}-
1: {
path: "imbot/_imbot.paUserName"
type: "string"
options: null
value: "mybuddy"
defaultValue: "mybuddy"
label: "IM ID"
description: "The ID under which ImBot feature is visible in the contact list."
}-
2: {
path: "imbot/imbot.paPassword"
type: "string"
options: null
value: null
defaultValue: null
label: "IM password"
description: "If IM server is configured to use LDAP you need to assign a dedicated account to play MyBuddy role. Set MyBuddy's password accordingly with LDAP account password. Leave the default password if IM server is not configured to use LDAP."
}-
-
}

```

Unsupported HTTP Method: PUT, POST, DELETE

View or modify My buddy settings

Available in 14 starting with 14.10

Resource URI: /imbot/settings/{settingPath}

Default Resource Properties:

The resource is represented by the following properties when the GET request is performed:

Property	Description

Specific Response Codes: N/A

HTTP Method: GET

Retrieves My buddy options for the setting from the specified path.

Example: XML format

```
<Setting>
<path>imbot/_imbot.paUserName</path>
<type>string</type>
<value>mybuddy</value>
<defaultValue>mybuddy</defaultValue>
<label>IM ID</label>
<description>The ID under which ImBot feature is visible in the contact list.</description>
</Setting>
```

JSON format

```
{
  path: "imbot/_imbot.paUserName"
  type: "string"
  options: null
  value: "mybuddy"
  defaultValue: "mybuddy"
  label: "IM ID"
  description: "The ID under which ImBot feature is visible in the contact list."
}
```

HTTP Method: PUT

Modifies My buddy options for the setting from the specified path.

HTTP Method: DELETE

Deletes My buddy options for the setting from the specified path.

Unsupported HTTP Method: POST